

WATCHDOGW120

The WatchDog NXT120 is capable of 120 pints per day, making it ideal for whole home applications. The NXT120 is ducted on both the inlet and outlet and can maintain areas up to 21,000 cubic feet. The NXT120 utilizes a gravity drain system and has duct collars on the inlet and the outlet.



- + UP TO 21,000 CUBIC FEET
- + ALUMINIUM COILS
- + DIGITAL DISPLAY
- + EASY TO MANEUVER

- + COMPLETE 5 YEAR WARRANTY
- + DUCT UP TO 10 FEET
- + LOW TEMP. OPERATION
- + AUTO RESTART

Rated Condensate Capacity (80°F, 60%)	120 ppd
Rated Condensate Capacity (73°F, 60%)	89.7 ppd
COP (73°F, 60%)	2.0 L/kWh
Refrigerant	R32
F.L.A. at Rated Conditions (80°F, 60%)	7.8A
Airflow @ 0.00" S.P.	225CFM
Inlet Filter	MERV-10
Supply Duct	10" Collar
Return Duct	10" Collar

Sound Level	59dBa
Drain Tube	6'
Coverage Area	21,000ft ³
Power Cord	10'
Operating Temperature Range	33 - 105° ^F
Operating Relative Humidity Range	36 - 90%
Weight	74 lbs.
Dimensions L x W x H (inches)	23.75 x 14 x 16
Warranty	Five Years
Power Supply	115V/60 Hz